729R

SFIC: Showcase, Ratchet Lock

BEST

For BEST style interchangeable core cylinders

ANSI/BHMA: Complies with clause 6.3 (8.2~8.4) of ANSI/BHMA A156.11 ANSI standards

US26D Finish

SPECIFICATIONS

Retrofits: Best 3S
ANSI/BHMA: Complies with clause 6.3 (8.2~8.4) of ANSI/BHMA A156.11 ANSI standards
Use: Sliding glass or wood doors
Body: Zinc die cast
Strap: Steel
Finish: 26D
Packaged: Packed 10 per box

KEYING INFORMATION

Cores: Not included.
Accepts: Best, Arrow, Falcon, KSP, Schlage SFIC or equivalent small format interchangeable cores
Compatible electronic cylinders: Medeco Nexgen XT or VIDEX CyberLock SFIC cylinders

INCLUDED ACCESSORIES

729RS-1 strap for 3/16" to 1/4" material thickness
725-1 spacer to fit 6 or 7 pin cores
725-PA plastic thumbturn

OPTIONAL ACCESSORIES

Alternate straps: 729RS-2 strap for 3/8" material thickness, or 729RS-3 strap for up to 5/8" material thickness
SFIC cores: 206/207 Series

INCLUDED ACCESSORIES

725-PA

725-1

WARNING: This product can expose you to chemicals including chromium, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

OLYMPUS LOCK INC

729R

SFIC: Rim Latch Door & Drawer Cabinet Lock

ANSI/BHMA:
Complies with clause 6.3 (8.2~8.4) of ANSI/BHMA A156.11 ANSI standards

OPTIONAL ACCESSORIES - *See our website for a complete list of optional components.*

206/207 Series

- 206 Series 6-pin SFIC cylinder
- 207 Series 7-pin SFIC cylinder

BEST compatible interchangeable core cylinders

AVAILABLE KEYWAYS

A	B	C	D	E	F	G	H	
J	K	L	M	Q	1C	1D	KMT300	

Alternate straps (available separately)
All straps are 6″ in length.

- 729RS-2 strap for 3/8″ material thickness
- 729RS-3 strap for up to 5/8″ material thickness

729RS-2 strap for 3/8″ material



729RS-3 adjustable strap for 3/8″ to 5/8″ material



DIMENSIONS | TYPICAL INSTALLATION





© 2019 Olympus Lock, Inc. | www.olympuslock.com | 800-525-0954

OLYMPUS LOCK INC