B7 SERIES

3/4" Cam Lock With BEST keyways



Available BEST Keyways A, B, E, F, G, J, K, L and R

This product is available in keyways that match existing BEST original keyways and can be keyed into existing systems using these BEST keyways.

SPECIFICATIONS

Function: Cam lock

Rekeyable: Easily rekeyable via cylinder retainer

clip

US Patent Nos: 5,038,589; 5,737,950

Retrofits: Best 5E

Usage: Commonly used as locking device on medical carts (see also our 724VR medical cart/file

cabinet lock for use on medical carts)

Body: Zinc die cast

Cylinder: Zinc die cast pin tumbler, drilled for 7 pins Standard function: Key removable in locked or

unlocked position.

Key retaining function: Alternate key-retaining shifters are available separately for key removable

in locked position only

Cams: 2 reversible cams work in all positions

Finish: 26D

Packaged: Packed 10 per box

KEYING INFORMATION

Keyways: A,B,E,F,G,J,K,L,R **Keys:** Includes 2 keys per lock

Stock keying: O-Bit

Keying: Custom and/or masterkeying available. Specify at time of order. Can be keyed into existing BEST SFIC systems using the same keyway.

INCLUDED ACCESSORIES

Trim collar

Straight cam #DCNP-100-SC Offset cam #DCNP-100-BC Anti-rotation plate #DCNP-500-ARP

OPTIONAL ACCESSORIES

Alternate cams

Key retaining drawer cam shifter #DCNP-100-KR Key retaining door cam shifter #DCNP-100-KDR

B7

Keyway: Available in 9 popular BEST keyways. Can be used in existing BEST systems using the keyways indicated.

Retrofits: Equivalent to BEST 5E Series. Handing: Includes 2 cams that work in all handings (door or drawer)



AVAILABLE KEYWAYS




B7 SERIES FEATURES


- Non-handed—Field reversible locking positions: right-hand, lefthand, vertical and inverted
- Only 2 cams required—Ships with reversible straight and offset cams that meet requirements of all locking positions
- Easy rekeyability—Allows for a quick installation and increased productivity
- Anti-rotation plate—Eliminates lock rotation, prevents loosening of fixing nut, and provides additional security in particleboard applications

INCLUDED CAMS 5/16" 5/8" 3/32" 5/8" 3/32" DCNP-100-SC DCNP-100-BC











B7 SERIES

3/4" Cam Lock
With BEST keyways



OPTIONAL ACCESSORIES - See our website for a complete list of optional components.

Other Accessories

Key-retaining cam shifters

- For door function: DCNP-200-KDR
- For Drawer function: DCNP-200-KR

Washers

- Pronged wood washer: DCNP-SPW
- Self-adhesive clear plastic washer for mounting lock on glass: DCNP-GW

Finger Pull

Finger pull: DCNP-300-FP

Number Plates & Kits

- T37-NKIT number plate kit
- T37DC-NP number plate only



T37-NKIT Number Plate KitIncludes both pieces.
For number plate only, use item # T37DC-NP



self-adhesive clear plastic washer for mounting lock on glass

DCNP-300-FP

TRB7 Series Trim Collars














Optional Cams

Note: Offset cams are reversible and can be used in either the inbent or outbent position.


Item	Description / Packed Each	
DCNP-HD-875	7/8" long straight cam	
DCNP-HD-1	1" long straight cam	
DCNP-100-SC	1-1/4" long straight cam	
DCNP-100-SC2	1-3/4" long straight cam	
DCNP-100-SC3	1-1/2" long straight cam	
DCNP-100-LC	3" long straight cam	


Item	Description / Packed Each	
DCNP-100-B1	Straight cam with oval cutout	
DCNP-100-B2	U-shaped cam	
DCNP-100-B3	Straight hook cam	
DCNP-100-WB	Short cam / 90° offset arm	

Item	Description / Packed Each	
DCNP-100-BC DCNP-100-BC5 DCNP-100-HC1 DCNP-100-HD DCNP-100-HD2 DCNP-100-HD3	1-1/4" long cam, 5/16" offset 1-1/4" long cam, 1/2" offset 1-1/2" long hook cam, 5/16" offset 1-7/16" long cam, 1/2" offset 1-3/4" long cam, 5/16" offset 1-1/8" long cam, 5/16" offset	
DCNP-100-LBC	1-1/2 long cam, 5/16" offset	

>> Visit our website **www.olympuslock.com** for complete dimension and descriptions of available optional cams.

DIMENSIONS | TYPICAL INSTALLATION





With Trim Collar		
For Mat. Thickness	7/8"	
Straight Cam (X)	1-3/16"	
Inbent Cam (Y)	7/8"	
Outbent Cam (Z)	1-1/2"	
Cylinder Length (A)	1-1/8"	

